

4 Seasons

High quality 100% acrylic paint
for exterior use



THINNING
5-10%



COVERAGE
11-13m²/L



TOOLS
brush, roller,
airless
spray gun.



DRY TO TOUCH
1-2 hours



High quality 100% acrylic paint for exterior use. Thanks to its advanced technology, the surface remains clean longer, as it is highly resistant to picking-up dirt and pollutants. It is highly resistant to weather conditions (sunlight, rain) and air pollution, thus offering long-lasting durability. It offers to the surface a water vapor permeability which prevents the build-up of moisture and mold. The white is certified as cool paint presenting high solar reflectance (SR), high infrared emittance (ϵ) and high solar reflectance index (SRI) reducing significantly the temperature of the walls during summer. The thousands of vibrant shades last in time and resist to fading due to solar UV radiation. It is easy to apply with high hiding power, as well as strong adhesion to mineral walls such as plaster, concrete, plasterboard and wood. Finally, it offers high film-building ability, for a smooth mat finish on the wall.

- » All weather Resistance
- » Brilliant white and vibrant colors
- » High Solar Reflectance and Durability to solar radiation

TECHNICAL DATA

Binder Type	Pure Acrylic
Specific Gravity {ISO 2811 @ 25°C}	1.29 - 1.43 kg/L*
Solids Content w/w {ISO 3251-03}	59% (± 3)*
Stormer Viscosity {ASTM D 562-05 @ 25°C}	115KU (± 15 KU)*
Application Viscosity {ASTM D 562-05 @ 25°C}	85 KU (± 15 KU)*
Gloss 60° {ISO 2813-99}	<5.0 units
Gloss 85° {ISO 2813-99}	<13.0 units*
pH	8.6-9.7
Water absorption w {EN 1062-3}	<0.05Kg/m ² h ^{0.5} Class w ₃
Water vapour permeability {EN 7783-2}	sd (m) <0.1 Class I
Whiteness Index {ASTM E 313-98}	89.5 (± 1.5) **
Yellowness Index {ASTM E 313-98}	0.4 (± 0.5) **
Solar Reflectance (TSR) {ASTM G 173}	0.89 **
Infrared Emittance (ϵ) {ASTM E 408-71}	0.92
Solar Reflectance Index (SRI) {ASTM E1980}	113 **
Coverage per coat	11-13 m ² /L***
Recommended Dry Film Thickness (2 coats)	70 μ m (± 5)

* Depending on the tinting base and the shade

** Only for White

*** Depending on the shade the application conditions and surface absorption



Exterior walls of mineral substrate A/c (WB)

- VOC Limit Value: 40g/L
- Maximum content of VOC of the product in a ready to use condition: 39g/L

4 Seasons

High quality 100% acrylic paint
for exterior use



SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, clean and free of dust, grease, residues, blistered paint etc. Wet sanding is recommended for the surface preparation.

- » **On new surfaces:** before applying the topcoat, apply one coat of a primer such as KRAFT ECO DUR AQUA or Kraft DUR.
- » **On surfaces that need filling:** use KRAFT SPACHTEL or KRAFT PUTTY.
- » Allow new plaster or concrete to surfaces to cure a minimum of 30 days prior to paint application.

APPLICATION INSTRUCTIONS

- » Avoid applying in case of expected rain in the next 4 days.
- » Before you start painting, dilute the paint by adding up to 5-10% by volume tap water and stir well.
- » Appropriate application tools for this product are brush, roller and airless spray gun.
- » The product be tinted with KRAFT INSPIRED COLOR tinting system to thousands shades. To ensure product quality required painted the corresponding base selected from the tinting system of KRAFT.
- » It is strongly recommended to be tinted with F-shades taken from KRAFT INSPIRED COLLECTION for high weather resistance or with the innovative shades of KRAFT REFLECTIVE COLLECTION for high weather resistance, certified from National Technical University of Athens for their high Total Solar Reflection (TSR%).
- » For shade and finish consistency, it is advisable to use containers of the same batch number. In case of different batch number it is recommended that they be mixed in a large container.
- » Apply two coats of KRAFT 4 SEASONS™ for the best result.
- » **Minimum recoat time:** 3-4 hours.
- » **Surface drying time:** 1-2 hours at 25°C and 50% relative humidity (drying times are longer in wet/cold conditions).
- » Avoid patching after finishing the painting. The difference of the substrate absorbance and application method might cause colour or gloss deviations. If it is necessary to repair apply the paint to the whole surface.
- » Do not apply at temperatures below 5°C and above 35°C and above 65% relative humidity.

AFTER USE INSTRUCTIONS

- » Clean the tools thoroughly with water and soap.
- » Close the bucket to maintain in good condition for future use. Store before and after use in a cool place and away from sunlight or frost conditions.

PACKAGING

- » Available in White in 0.750L, 3L, 10L. Base P, T, D and A - in containers of 1L, 3L & 10L.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Read label before use. For further information please refer to the Material Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793777

STORAGE

- » Store the product at temperatures between 5°C to 35°C.

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.gr, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.gr



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm

Email: paints.orders@druckfarben.gr