

Go! Hydrochroma

White water-paint
for interior walls and ceilings



THINNING
8-12%



COVERAGE
8-10m²/L



TOOLS
brush,
roller



DRY TO TOUCH
1-2 hours



White water-paint with high whiteness and vapour permeability for interior walls and ceilings. Suitable for frequent repainting. It provides a uniform mat finish.

- » High whiteness
- » High vapour permeability
- » Suitable for frequent recoating

TECHNICAL DATA

Specific Gravity {ISO 2811 @ 25°C}	1.59Kg/L (±0.02)
Solids Content w/w {ISO 3251-03}	62% (±3)
Stormer Viscosity {ASTM D 562-05 @ 25°C}	120KU (±20)
Application Viscosity {ASTM D-562-05 @ 25°C}	85KU (±15)
Gloss 60° {ISO 2813-99}	<4 units
Gloss 85° {ISO 2813-99}	<19 units
pH	8.5-9.5
Whiteness Index {ASTM E 313-98}	90 (±1.5)
Yellowness Index {ASTM E 313-98}	0.5 (±0.5)
Coverage per coat *	8-10m ² /L
Recommended Dry Film Thickness (2 coats)	70µm (±5µm)

* Depends on substrate porosity, texture, painting conditions and application method.



Interior matt walls and ceilings A/a (W/B).

- EU VOC Limit Value: 30g/L
- Maximum content of VOC of the product in a ready to use condition: 29g/L

Go! Hydrochroma

White water-paint
for interior walls and ceilings



SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, clean and free of dust, grease, residues, blistered paint etc. Wet sanding is recommended for surface preparation.

- » **On new surfaces:** Before applying the topcoat, apply one coat of a water-based primer such as KRAFT ECO DUR AQUA or KRAFT DUR AQUA WHITE or KRAFT HAFT or KRAFT GO! plasterboard primer.
- » **On surfaces that need repairing:** Use KRAFT SPACHTEL or KRAFT PUTTY or the suitable repairing material of KRAFT.

APPLICATION INSTRUCTIONS

- » Before you start painting, dilute the paint 8-12% by volume with tap water and stir well.
- » Appropriate application tools for this product are brush and roller.
- » Apply two coats of Kraft Go! HYDROCHROMA for the best result.
- » **Surface drying time:** 1-2 hours at 25°C and 50% relative humidity (drying times are longer in wet/cold conditions).
- » **Minimum recoat time:** 4-6 hours.
- » Do not apply at temperatures below 5°C and above 35°C and above 65% relative humidity.
- » Go! HYDROCHROMA can be mixed with KRAFT MASTER BASICS for plenty of light shades. Apply two coats of KRAFT GO! HYDROCHROMA for the best result.
- » Avoid patching after finishing the painting. The difference of the substrate absorbance and application method might cause colour or gloss deviations. If it is necessary to repair apply the paint to the whole surface.

AFTER USE INSTRUCTIONS

- » The painted with KRAFT GO! HYDROCHROMA surface is not washable.
- » Clean the tools thoroughly with water and soap.
- » Close the bucket to maintain in good condition for future use. Store before and after opening in a cool place and away from sunlight or frost conditions.

PACKAGING

- » Available in White in 3L and 9L containers.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Read label before use. For further information please refer to the Material Safety Data Sheet.

Poison Centre Telephone:

+30 210 7793777

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.gr, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.gr



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm

Email: paints.orders@druckfarben.gr