

# White Spirit

High quality solvent



It is a high quality aromatic hydrocarbon solvent for thinning solventborne alkyd single component paints that are applied with brush or roller on wooden or metallic surfaces. It enhances the application properties of the paint and improves the through and surface drying. It is also suitable for degreasing the metallic surfaces before paint application or cleaning the painting tools after use.

- » Alkyd solventborne paints thinner
- » Enhances the application properties
- » Suitable for cleaning the painting tools

## TECHNICAL DATA

<b>Specific Gravity</b> {ASTM D4052 @ 15°C}	0.77-0.79Kg/L
<b>Solubility in water</b>	Insoluble



# White Spirit

## High quality solvent



### APPLICATION INSTRUCTIONS

#### ONLY FOR PROFESSIONAL USE

- » Product ready to use.
- » Use it outdoor or in a well-ventilated area.
- » Wear protective gloves, clothing, and eye/face protection equipment.
- » Dilute one component solventborne paints up to specific product indications.
- » Dilute and stir well the mixture before use.
- » Do not use at temperatures below 5°C and above 35°C.

### AFTER USE INSTRUCTIONS

- » Close the bucket well to maintain in good condition for future use. Store before and after opening in a cool place and away from sunlight or frost conditions.

### PACKAGING

- » It is available in 0.375L, 0.75L, 4L and 16L containers.

### HEALTH SAFETY AND ENVIRONMENTAL INFORMATION

Read label before use. For further information please refer to the Material Safety Data Sheet.

Poison Centre Tel:

**+30 210 7793777**

### STORAGE

- » Store the product before and after opening at temperatures between 5°C to 35°C and relative humidity <50%.

**DISCLAIMER:** The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.kraftpaints.gr](http://www.kraftpaints.gr), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

#### DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501  
[www.druckfarben.gr](http://www.druckfarben.gr) | [www.kraftpaints.gr](http://www.kraftpaints.gr)



Toll-free number

**800 111 7700** Monday - Friday, 8.00 am - 04.00 pm

Email: [paints.orders@druckfarben.gr](mailto:paints.orders@druckfarben.gr)