

Wood Style Aqua

Water based polyurethane
decorative wood varnish



THINNING
0-10%



SPREADING RATE
10-12m²/L



TOOLS
brush



DRY TO TOUCH
½-1 hour



It is a high quality waterborne polyurethane acrylic decorative varnish. It protects and decorates the wood. Suitable for exterior and interior wood surfaces such as doors, windows, frames, pergolas, fences. It presents an exceptional durability, stain removal properties and transparency. It has excellent application and leveling properties. The elasticity enables it to support dimensional variations without cracking or flaking.

- » **Strong Durability**
- » **Outstanding Transparency**
- » **High Elasticity and Hardness**

TECHNICAL DATA

Binder Type	Acrylic/Polyurethane	
Specific Gravity {ISO 2811 @ 25°}	1.04Kg/L(±0.02)	
Solids Content w/w {ISO 3251-03}	34% (±3)	
Viscosity-Flow Cup N°4 @25°C* {ISO 2431}	90-140sec	
pH	8.5-9.5	
Spreading Rate per coat**	10-12m ² /L	
Gloss @ 60° {ISO 2813-99}	Gloss	85-95 units
	Satin	35-45 units
	Mat	10-20 units

* Depending on the finish.

** Depending on the finish the application conditions and surface absorption.



Interior and exterior trim varnishes and woodstains, including opaque woodstains (A/e) (WB).

- Limit Value: 130g/L
- The maximum VOC content of the product in its ready to use condition: 129g/L

Wood Style Aqua

Water based polyurethane decorative wood varnish



SURFACE PREPARATION

The surface must be dry and free of dust, mold or resin. Sand with a suitable abrasive paper, along with the grain, and smooth well the surface.

- » **On new wooden surfaces:** Remove greases or resins with KRAFT BRUSH THINNER, sanding parallel to the grain, removing the dust with a damp, lint-free cloth, apply 1 coat of KRAFT WOOD CARE wood preservative for protection against woodworm and fungi. In case you need a color effect on wood apply before the varnish, 1-2 coats of KRAFT WOOD SHIELD.
- » **On painted surfaces:** Check the surface stability. If it is acceptable apply directly the varnish. If not, remove all old paint or varnish using KRAFT REMOVER and then clean the surface with KRAFT BRUSH THINNER or sand well until their removal with the appropriate sandpaper. After complete drying of the surface and removing all residues, repair all the defective points of the wood with suitable putty. Then apply the varnish.

APPLICATION INSTRUCTIONS

- » Before you start painting, dilute the paint by adding up to 10% by volume tap water and stir well.
- » Check the wood moisture before painting. It shall not exceed 10%.
- » Do not apply on wooden surfaces which are in contact with the ground or water.
- » The durability of the film is reduced when applied on horizontal surfaces that are pressed.
- » Appropriate application tool for this product is brush.
- » Apply 2 coats of KRAFT WOOD STYLE AQUA for the best result.
- » Minimum recoat time is approx. 24 hours.
- » The surface drying time is ½-1 hour at 25°C and 50% relative humidity (drying times are longer in wet/cold conditions).
- » Avoid application at temperatures below 10°C or greater than 35°C and relative humidity greater than 60%.

AFTER USE INSTRUCTIONS

- » Close the bucket well to maintain in good condition for future use. Store before and after opening in a cool place and away from sunlight or frost conditions.
- » Clean the tools thoroughly with water and soap.
- » Allow at least 15 days before cleaning and washing newly painted surfaces.
- » You can wash the painted surfaces gently with a soft sponge and water and in cases of bad stains with a mild detergent.

PACKAGING

- » Available in transparent gloss, satin and mat finish in 0.750L and 2.5L containers.

HEALTH SAFETY AND ENVIRONMENTAL INFORMATION

Read label before use. For further information please refer to the Material Safety Data Sheet

Poison Centre Telephone:

+30 210 7793777

STORAGE

- » Store the product before and after opening at temperatures between 5°C to 35°C.

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.kraftpaints.gr, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501
www.druckfarben.gr | www.kraftpaints.gr



Toll-free number

800 111 7700 Monday - Friday, 8.00 am - 04.00 pm

Email: paints.orders@druckfarben.gr